




SPRAY HOG

Commercial Diesel-Powered Hydraulic Airless Sprayer

The Spray Hog's patented system is specifically designed to make spraying waterproofing and vapor barrier coatings easy. The Spray Hog's self-contained heat source allows coating material to be heated in a single pass. This heat lowers the viscosity of the material for better spray application. The Spray Hog having its own self-contained heat source makes it very portable.



\$22,995.00 (Bare)



Package Includes:

*\$25,9*95.00



Spray Hog with "New 250cc Extreme Pump Lower" Kubota 18hp diesel with Siphon Side Heat Exchanger



High Pressure Hose - Insulated and Jacketed (200' x 1/2")



Graco Silver Plus Gun
 Z-Swivel & 6' x 3/8" Whip hose
 Heavy Duty RAC Housing
 Heavy Duty RAC Tip GHD539



Pole Extension (4')



Electric Rewind Hose Reel with Jump Hose

Spray Hog Specifications:

Maximum Flow Rate: 4gpm Maximum Output PSI: 4000psi

Pump Lower: 250 cc Extreme
Hydraulic Motor: Viscount II
Diesel Motor: Kubota 18hp

Fuel: Diesel 6 gallon tank

Weight: 925 lbs

Heat Exchanger: Tube-in-Shell

Battery: 12V Siphon Line 8' x 1.5"

Dimensions: 25"w x 61L" x 57T"